



• Mono input channels:	4
Micro (sensitivity / impedance)	- 60dB / 2,2 kΩ
Line (sensitivity / impedance)	- 40dB / 10 kΩ
Channel gain range	30dB
• Stereo input channels:	4
Line L/R (sensitivity / impedance)	- 46dB / 10KΩ
Channel gain range	34dB
• All channels:	
Equalization	H.F : ±15dB @ 15kHz (shelving) M.F: ±15dB @ 600Hz (peaking) L.F : ±15dB @ 50Hz (shelving)
Equivalent input noise	-128dB
Peak LED indicator	+ 17dB, 6dB before clipping
• External effect send	
Nominal level	0dB
Impedance	100Ω
Max level	+ 22dB
• External effect return	
Nominal level	-10dB
Impedance	10kΩ
Max level	+22dB
• Master outputs, L/R, Control room	
Nominal level	0dB
Impedance	100Ω
Max. level	+22dB
Min. load impedance	600Ω
Frequency response	25Hz ÷ 30kHz (+0 / -2dB)
THD	< 0,01%
SNR	82dB
• Aux outputs:	2 (1 pre + 1 post)
Nominal level	0dB
Max. level	+22dB
• Tape in:	
Nominal level	- 20dB
• Tape out:	
Nominal level	- 10dB
• Headphones:	
Load impedance	200 ÷ 600Ω
• Dimensions (W x H x D):	32,2 x 5 x 26,3 cm
• Weight:	2,5 kg